



## Features

- Made of lightweight double anodized aluminum
- Frosted lens protects light source while evenly diffusing light
- Field cuttable housing, insert, and lens
- Aluminum provides excellent heat dissipation
- Mounting clips and ends are available
- Compatible with all Trulux Tape Light

## Available Lengths

78-3/4" (2 meter)

## Available Finishes



Anodized Aluminum

## Compatible Tape Light

- Trulux Single Color
- Trulux Tunable CCT
- Trulux RGB / RGBW / RGB+TW

## TRULUX™ Mini Flange Slot Channel

For seamless lines of light that blends directly into the wall or substrate, the mini flange channel is a premium solution for applications where modern clean lines of light are a must. Simply pre-install dedicated housing slots during new construction drywalling phase and snap in the finished channel and lens. Once completed, all you are left with is a stunning line of light incorporated into the wall or substrate.

### Best suited applications:

Ceilings, wall slots, hallways, corridors, lobbies, theaters, and accent lighting

## Ordering Information

<b>PE-D.5-2M</b>	1/2" Drywall Rough-in Housing
<b>PE-D.6-2M</b>	5/8" Drywall Rough-in Housing
<b>PE-SLOT-2M</b>	Mini Flange Insert
<b>PE-SLOTLENS-2M</b>	Frosted Polycarbonate UV Lens
<b>PE-SLOT-END</b>	Mini Flange Slot End Cap
<b>PE-SLOT-CLIP</b>	Mini Flange Slot Clip (Required)
<b>PE-FC-END</b>	Drywall Slot Housing End Cap

