

## WARRANTY PERIODS BY PRODUCT CATEGORY

PRODUCT CATEGORY	WARRANTY PERIOD	AVERAGE LIFE IN HOURS*	PRICE PAGE(S)
Trulux Tape Light	5 years	50,000	6-18
Trulux Tape Light Kits	5 years	50,000	5
Trulux Controller	3 years	35,000	6-18
Trulux Receivers	5 years	35,000	6-18
MicroLink Seamless Bar Light	3 years	30,000	21
Tunable EdgeLink Flat Panel	5 years	35,000	22
EdgeLink Flat Panel	5 years	35,000	23
LED-3 Complete Undercab	5 years	35,000	24
LED Complete 2 Undercab	5 years	35,000	25
Priori Xenon Undercabs	1 year	8,000	26
Tunable Omni Puck Light	3 years	30,000	27
Omni Puck Light	3 years	30,000	27
MVP Puck Light	3 years	50,000	28
Mini Recessed	3 years	30,000	29
LED Downlights - Epiq Mag	5 years	50,000	30
LED Downlights - All Types, All Sizes	5 years	35,000	29-34
Hybrid2 & Hybrid 2 RGB	1 year <sup>†</sup>	30,000	37-39
Polar 2 Neon, Polar 2 RGB, & Polar 2 Mini	1 year <sup>†</sup>	30,000	40-42
LED FlexBrite Kits	1 year**	60,000	43
LED FlexBrite Custom Cut	1 year	60,000	43
LED FlexBrite Reels	1 year <sup>†</sup>	60,000	44
LS2 Commercial Grade Light String	1 year	Depends on lamps used	45
Commercial Grade Light String (Non-ETL)	1 year	Depends on lamps used	45
Festoon Light String	3 years	80,000 (12), 20,000 (24V)	46
LED LightStar Reels	1 year <sup>†</sup>	50,000	46
Standard LED S14	1 Year	25,000	47
Professional LED Decorative Lamps	3 years	25,000	47
FrameWRX Exterior Series	5 years <sup>††</sup>	30,000	48
Brick Light	2 years	50,000	49
SGL3 Step Light	2 years	50,000	49
Inner Square Step Light	2 years	30,000	50
Panorama Sentry Series	3 years	50,000	50
Panorama Sunset Series	3 years	50,000	50
Radar Swivel	3 years	50,000	50
Wedge	3 years	50,000	50
Wall Washers	3 years	40,000 (WW) 60,000 (RGB)	51
Constant Voltage Power Supplies	2 years	N/A	52-56
Constant Current Power Supplies	2 years	N/A	52-56
Magnetic Transformers	3 years	N/A	52-56

### \*AVERAGE LIFE

Average incandescent lamp life, rated life and average life are terms used to describe the number of hours at which half of the lamps have failed. For LEDs, the hours of rated life specify the point where 70% of original lumen output is reached. Below this point, the effective life is over, however, the LED may still emit light. Individual results may vary with actual environmental conditions including, but not limited to, proper installation, ambient temperature and/or input voltage fluctuations.

<sup>†</sup>Standard Linear Warranty applies. See back page for details.

\*\*Limited Product Warranty applies to lengths up to 75 feet. See back page for details.

<sup>††</sup> Warranty life based on average 3 hours/day use, 7 days/week.

## LIMITED PRODUCT WARRANTY

Our products are warranted to be free from defects in material and workmanship for the warranty period listed on the reverse by product category. Warranty periods begin from the date of shipment from American Lighting Inc's warehouse to the original purchaser. Products that prove to be defective during their specific warranty period will be either repaired or replaced, at the sole discretion of American Lighting Inc. Claims for defective products must be submitted in writing to American Lighting Inc's RGA Department within the warranty period. Upon approval of such return, American Lighting Inc reserves the right to inspect the product for misuse or abuse. Claims for indirect or consequential damages or for product that, in American Lighting Inc's opinion, has been misused will be denied. This is a warranty of product reliability only and not a warranty of merchantability or fitness for a particular purpose. American Lighting Inc shall have no liability whatsoever in any event for payment of incidental or consequential damages, including, without limitations, installation costs and/or damages for personal injury and/or property. These products may represent a possible shock or fire hazard if improperly installed or altered in any way. This warranty does not apply to any product that has not been properly installed in accordance with current local codes and/or the National Electrical Code. Products that require a transformer, driver or power supply must be used in conjunction with American Lighting Inc's recommended power supply to ensure safety and retain product warranty.

## STANDARD LINEAR WARRANTY

Rope light and linear lighting products in all their various types and shapes, whether LED or incandescent, are wired in series parallel. This means that several individual lamps or LEDs are wired together in series to equal 12V, 24V or 120V. Then these sections are wired together (in parallel) to light up in unison. If one solder joint, lamp or resistor fails, a whole section will not light. Due to the number of elements involved, and the numerous extenuating circumstances beyond our control, American Lighting Inc offers a Standard Linear Warranty on most linear lighting products. The limited liability warranty is listed above, however the Standard Linear Warranty offers replacement product *by section* due to defective material and/or workmanship for one year beginning from the date of shipment from American Lighting Inc's warehouse to the original purchaser.

## USE OF LINEAR LIGHTING IN OUTDOOR APPLICATIONS

Incandescent rope light and LED Flexbrite UL 2388 custom cuts; incandescent and LED Flexbrite pre-packaged kits; and UL Listed (special order) cuts of LED Neon Flexbrite Plus and Economy have factory assembled power connections and end caps that seal the rope from moisture. Due to strict quality control standards, American Lighting is able to offer a limited warranty on these items rather than the standard linear lighting warranty that replaces product by defective section only. For outdoor applications, best practices include using kits interconnected (same length kits are best for color control of White LED Flexbrite) or using custom cuts that do not exceed 75 feet.

For all linear lighting categories, any non-rated field connection made in an outdoor application should be properly sealed with dielectric grease covering all conductive materials; and properly installed power connections and end caps, sealed with silicone and heat shrink tube. However, since non-rated (field executed) power connections of linear lighting products cannot be quality controlled, and outdoor use of non-rated product is not recommended, American Lighting cannot warrant the product to any purchaser.

## PRODUCT SPECIFICATIONS

For the latest product information, updates, instructions and details concerning specifications, colors, finishes, performance, installation and design, visit [www.americanlighting.com](http://www.americanlighting.com). Color may vary from the color printed herein due to limitations in photographic and printing processes. American Lighting Inc. reserves the right to change product specifications without notice. Other product specifications such as color temperature, wavelength characteristics and lumen output are subject to production limitations and may vary.

LED technology is changing rapidly, and not all color temperatures and performance levels can be duplicated at a later time. Best practices include purchasing 10-15% more for a particular project on the same initial order where white LED color temperatures must be maintained over project and product life. Eventual product replacement should be considered at layout and design stages. Best practices also include testing connections and product performance prior to mounting and/or installing.